


**Conical
Rings**

Available in the best high carbon-high chrome core hardened steel or in sintered metal.



**Tapes, Belts,
Straps**

Complete line of spindle tapes and drive belts, light-weight conveyor belts and pulling straps.



Traveler Hooks & Ring Knives

For installing travelers and devices for removing waste.



Spin Cleans

Designed to remove fly and fiber waste safely from rolls and hard to reach machine areas.



Trusted for the Long Run

**STEEL
TRAVELERS**
J (Conical) & HZ (Vertical)



....FOR LONG STAPLE
SPINNING AND
TWISTING!



A. B. Carter, Inc.
4801 York Highway
Gastonia, NC 28052 USA





Tel: (704) 865-1201
Fax: (704) 864-8870




E-mail: sales@abcarter.com
Website: www.abcarter.com

Nov-2018


... Both **J Type (Conical)** and **HZ (Vertical)** are offered in specific sizes and styles to assure optimum performance in all spinning and twisting applications. Our travelers are manufactured from the highest quality raw materials to assure consistent performance and excellent wear resistance. Made to fit all ring profiles along with a mirror polished surface, **CARTER TRAVELERS** give you the best combination of quality and performance.



J Type Traveler for Conical Ring



HZ Type Traveler for Vertical Ring



AVAILABLE FINISHES	APPLICATION
BRILLIANT	High polished surface to enhance yarn quality and runnability on all fiber types.
MIRACLE	Special nickel finish to enhance wear resistance and prevent corrosion.
CPH (CHROME PLATED HEAD)	Chrome plated (head only) for maximum wear resistance on abrasive fibers.

TABLE COMPARING WEIGHTS AND NUMBERS

CARTER		REINERS+FUST		BRACKER		CARTER		REINERS+FUST		BRACKER	
ISO NO	R+F NO	ISO	BRACKER NO	ISO	ISO NO	R+F NO	ISO	BRACKER NO	ISO		
12	40	11.8	-	-	68	25.5	67	25	71		
13.5	39	13.2	38	14	75	25	75	-	-		
15	38	15	-	-	84	24.5	85	24.5	80		
16.5	37	16	37	16	92	24	90	24	90		
18	36	18	36	18	105	23.5	100	23.5	100		
19.5	35	20	35	20	110	23	112	23	112		
21	34	21.2	34	21	120	22.5	118	22	125		
22.5	33	22.4	32	22.4	130	22	132	-	-		
24	32	23.6	-	-	140	21.5	140	21.5	140		
26	31	26.5	31	25	150	20.5	150	-	-		
29	30	30	30	28	165	20.5	160	21	160		
31	29.5	31.5	29	31.5	180	20	180	20	180		
33	29	33.5	-	-	210	-	-	-	200		
36	28.5	35.5	28.5	35.5	230	19.5	224	19.5	224		
39	28	40	28	40	255	19	250	19	250		
44	27.5	45	27.5	45	300	18.5	300	18.5	280		
48	27	50	27	50	350	18	355	18	355		
54	26.5	53	26.5	56	400	17.5	400	17.5	400		
60	26	60	26	63	450	17	450	17	450		

Other Weights Available Upon Request

RING HEIGHTS AVAILABLE


J TYPE (CONICAL)			HZ TYPE (VERTICAL)		
9.1mm (23/64")	11.1mm (7/16")	17.0mm (43/64")	9.5mm (3/8")	10.3 (13/32")	17.0mm (43/64")

Wire Profile and Application


Round "RW" - For processing fine count Wool and Synthetics

Flat "F" - For heavy count Wool and Synthetics


Oval - For medium and coarse wool and synthetic counts



"RW"



"F"



"OVAL"